



Shenzhen Anbotek Compliance Laboratory Limited

R011606189L

# INPUT POWER TEST REPORT


For

**AOK LED Light Company Limited**

Building 1, St George's Science and Technology Industrial Park, Shajin Street, Shenzhen, Guangdong Province, China

AOK-150WiU

<b>This Report Concerns:</b> <input checked="" type="checkbox"/> Original Report	<b>Equipment Type:</b> LED High Bay Light
<b>Test Engineer:</b> Rain Chen <i>Rain Chen</i>	
<b>Report No:</b> R011606189L	
<b>Date of Receipt:</b> 2016-06-06	
<b>Test Date:</b> 2016-06-07 to 2016-06-22	
<b>Report Date:</b> 2016-06-24	
<b>Reviewed By:</b> Raymond Song/Energy Lab Manager <i>Raymond Song</i>	
<b>Prepared By:</b> Shenzhen Anbotek Compliance Laboratory Limited	
1/F., Building 1, SEC Industrial Park, No.0409 Qianhai Road, Nanshan District, Shenzhen, Guangdong, China.	



Note: This test report is specially limited to the above client company and product model only. It may not be duplicated without prior written consent of Shenzhen Anbotek Compliance Laboratory Limited.. This report must not be used by the client to claim product endorsement by NVLAP, NIST or any agency of the U.S. Government. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.



**General Product Information:**

LED driver:

The luminaires contained the following driver models :

Name of lighting	Name of Driver	Model of Driver
LED High Bay Light	LED Driver	HBG-160-48A




**Input Test Report**

**TEST PROCEDURE**

1. Set up the test circuit according to the test circuit diagram below;
2. Adjust the Ac source to 100V/50Hz and operated for at least 30 minutes;
3. Read the input data(current, wattage and power factor) from the Ac power meter and the output data from the d.c. power meter(voltage, current, wattage and power factor);
4. Adjust the Ac source to 220V/50Hz and operated for at least 30 minutes and repeat step three;
5. Adjust the Ac source to 230V/50Hz and operated for at least 30 minutes and repeat step three;
6. Adjust the Ac source to 240V/50Hz and operated for at least 30 minutes and repeat step three;
7. Adjust the Ac source to 100V/60Hz and operated for at least 30 minutes and repeat step three;
8. Adjust the Ac source to 220V/60Hz and operated for at least 30 minutes and repeat step three;
9. Adjust the Ac source to 230V/60Hz and operated for at least 30 minutes and repeat step three;
10. Adjust the Ac source to 240V/60Hz and operated for at least 30 minutes and repeat step three.

**TEST CIRCUIT DIAGRAM:**



**TEST AMBIENT:** 25°C, 60%RH

The Lighting was allowed to operate for at least 30 minutes before the measurements were taken.

**TEST EQUIPMENT LIST:**

Device	Manufacture	Model No	Serial No	Test Range	Calibration date	Calibration due date
AC Power Source	ALL POWER	APW-110N	997079	0-300V, 0-1000VA	2016-04-06	2017-04-05
Digital Power Meter	YOKOGAWA	WT210	-	0-600V/0-10A/0-100Hz	2016-04-06	2017-04-05
Electronic Loading	SE-522	CD8612T	-	-	2016-03-14	2017-03-13



TEST DATA:

Test Model:					AOK-150WiU			
Sample No.					1#			
Input					Output			
Voltage (V)	Frequency (Hz)	Current (A)	Wattage (W)	Power factor	Voltage (V)	Current (A)	Wattage (W)	Power factor
100	50	1.664	166.0	0.996	45.43	3.303	150.1	1
220	50	0.752	161.6	0.976	45.43	3.303	150.1	1
230	50	0.721	161.6	0.972	45.43	3.303	150.1	1
240	50	0.693	161.6	0.969	45.43	3.303	150.1	1
100	60	1.670	166.7	0.997	45.43	3.303	150.1	1
220	60	0.756	162.0	0.973	45.43	3.303	150.1	1
230	60	0.726	162.0	0.969	45.43	3.303	150.1	1
240	60	0.698	161.8	0.963	45.43	3.303	150.1	1

Annex A-EUT photos

A1- Whole view of EUT



A2- Top view of Driver



-----End of Report-----